

SPI-M600

Grundfos® Pump Seal
Technical Data Sheet



Features

Grundfos® Pump Types
spi® Seal Type GR-706C can be used in Grundfos® Pump
For more information, please do not hesitate to contact
our Technology department

spi® Seal Type GR-706C can be used in Grundfos® Pumps JP, CH8, CH12, CRK12, CRK14, SPK1, SPK2, SPK4, SPK8, CR2,CR4 series pump, with shaft size 12mm

Combination Materials

1. Rotary Face

- Reaction Bonded Sic RBSIC **O**
- Sintered Silicon Carbide SSIC **O₁**
- Tungsten Carbide. Ni-binder **W**

2. Stationary Seat

- Carbon graphite, resin impreg **A_k**
- Carbon graphite,antimony impreg **A_D**
- Reaction Bonded Sic RBSIC **O**
- Sintered Silicon Carbide SSIC **O₁**
- Tungsten Carbide. Ni-binder **W**

3. Auxiliary Seal

- EPDM **E**
- FKM **V**
- NBR **P**

4. Spring

- GrNi-Steel (AISI304) **F**
- GrNiMo-Steel (AISI316) **G**

5. Metal Parts

- GrNi-Steel (AISI304) **F**
- GrNiMo-Steel (AISI316) **G**