

# SPI-M665

HIDROSTAL® Pump Seal  
Technical Data Sheet



## Features

HIDROSTAL® Pump Types

spi® Seal Type SPI-M665 can be used in Grundfos® Pumps

For more information, please do not hesitate to contact our Technology department

## Combination Materials

### 1. Rotary Face

Reaction Bonded Sic RBSIC O

Sintered Silicon Carbide SSIC O<sub>1</sub>

Carbon graphite, resin impreg A<sub>K</sub>

Carbon graphite, antimony impreg A<sub>D</sub>

### 2. Stationary Seat

Reaction Bonded Sic RBSIC O

Sintered Silicon Carbide SSIC O<sub>1</sub>

Aluminium Oxide Ceramic B

### 3. Auxiliary Seal

EPDM E

FKM V

NBR P

### 4. Spring

GrNi-Steel (AISI304) F

GrNiMo-Steel (AISI316) G

### 5. Metal Parts

GrNi-Steel (AISI304) F

GrNiMo-Steel (AISI316) G

spi® Seal Type SPI-M665 can be used in Grundfos® Pumps Usually can be used with HI-C or HI-X seal in tandem. With shaft size 15.87mm, 20.0mm, 20.0mm, 28.57mm, 38.10mm, 50.80mm, 63.50mm, 76.20mm, 95.0mm and 100.0mm