

SPI-M695

LOWARA® Pump Seal
Technical Data Sheet



Features

I.T.T. LOWARA® Pump Types
spi® Seal Type LOW-SPI-M695 can be used in I.T.T.
LOWARA® Pumps
For more information, please do not hesitate to
contact our Technology department

spi® Seal Type LOW-SPI-M695 can
be used in I.T.T. LOWARA® Pumps
SV, SVI, e-SV Series Pump with shaft
size 12mm, 16mm and 25mm

Combination Materials

1. Rotary Face

- Reaction Bonded Sic RBSIC **O**
- Sintered Silicon Carbide SSIC **O₁**
- Tungsten Carbide. Ni-binder **W**

2. Stationary Seat

- Reaction Bonded Sic RBSIC **O**
- Sintered Silicon Carbide SSIC **O₁**
- Carbon graphite, resin impreg **A_K**
- Carbon graphite,antimony impreg **A_D**

3. Auxiliary Seal

- EPDM **E**
- FKM **V**
- NBR **P**

4. Spring

- GrNi-Steel (AISI304) **F**
- GrNiMo-Steel (AISI3 16) **G**

5. Metal Parts

- GrNi-Steel (AISI304) **F**
- GrNiMo-Steel (AISI3 16) **G**