

SPI-M730

TSURUMI® Pump Seal
Technical Data Sheet



Features

TSURUMI® Pump Types

spi® Seal Type TSU-SPI-M730 can be used in TSURUMI® Pumps

SPI-M730 can be used in EBARA® Pumps, HANJIN® Pumps

For more information, please do not hesitate to contact our Technology department

Combination Materials

1. Rotary Face

Reaction Bonded Sic RBSIC ○

Sintered Silicon Carbide SSIC ○₁

Carbon graphite, resin impreg A_K

Carbon graphite, antimony impreg A_D

2. Stationary Seat

Reaction Bonded Sic RBSIC ○

Sintered Silicon Carbide SSIC ○₁

Ceramic B

3. Auxiliary Seal

EPDM E

FKM V

NBR P

4. Spring

GrNi-Steel (AISI304) F

5. Metal Parts

GrNi-Steel (AISI304) F

spi® Seal Type, TSU-SPI-M730 can be used in TSURUMI® Pumps With shaft size 14mm, 20mm, 30mm, 35mm, 40mm, 45mm and 50mm. TG-4702 to suit EBARA Pumps, HANJIN Pumps With shaft size 13mm, 14mm, 15mm, 16mm, 20mm, 25mm, 30mm, 35mm, 40mm, 45mm and 50mm.